

Product

Bugle Head Self Drilling Screws

Fine Thread - Square Drive

Description

Bugle head self drilling screws are used to fasten thick polystyrene cladding panels to steel. The self embedding bugle head with flat top allows the screw heads to be rendered over after installation, leaving a smooth surface finish.



Technical Properties

Material:	SAE 1022 Steel
Surface Hardness:	560 HV (min)
Case Depth:	0.10-0.23 mm
Torsional Strength:	5.4 Nm
Protective Coating:	Ruspert Silver Grey
Corrosion Testing Method:	Neutral Salt Spray Test w/ min. requirements of <5% red rust after 1000 hrs. of testing

Product Range

SIZE GAUGE-TPI × LENGTH	DRILL CAPACITY	DRIVE SIZE	THREAD LENGTH	PACK QTY	PART NUMBER
10-12 × 75 mm	0.6 mm	#2 SQ	66 mm	500	PNB310075-SQ
10-12 × 105 mm	0.6 mm	#2 SQ	66 mm	500	PNB310100-SQ
10-12 × 130 mm	0.6 mm	#2 SQ	86 mm	500	PNB310130-SQ
10-12 × 150 mm	0.6 mm	#2 SQ	100 mm	500	PNB310150-SQ
10-12 × 165 mm	0.6 mm	#2 SQ	100 mm	500	PNB310165-SQ
10-12 × 185 mm	0.6 mm	#2 SQ	100 mm	500	PNB310185-SQ

MELBOURNE

Phone 03 9543 8422
Fax 03 9543 4431
sales@trifixx.com.au

GEELONG

Phone 03 5282 1755
Fax 03 5282 6090
saleslara@trifixx.com.au

SYDNEY

Phone 02 9677 9029
Fax 02 9677 9023
sales@trifixxsw.com.au

trifixx.com.au