

M8 HEAVY DUTY SELF DRILLING SCREW

- Premium quality self drilling screw to replace conventional fixing by bolts & nuts
- Shear strength of 18.3kN, double that of regular 14g self drilling screws
- M8 x 35mm & M8 x 65mm
- 20 TPI (threads per inch)
- No pre-drilling required, ideal for blind fixing
- Available in galvanized silver finish suitable for both internal and external use.
- Drill point for self drilling into heavy gauge steel (2.3-7.0mm)
- Heavy duty hex head (12mm A/F)
- Guaranteed performance
- Time saving and trouble free
- Recommended drill speed 1800 RPM

	Tensile Strength (kN)	Shear Strength (kN)	Pull-Out Strength (kN)			
			2.30mm	3.20mm	4.50mm	6.00mm
M8	30.14	18.97	5.15	8.31	14.14	22.99
	31.24	18.30	4.91	8.15	15.24	23.38
	32.26	18.79	5.00	8.65	14.85	21.99
	31.08	19.37	5.31	8.10	14.34	21.52
	32.82	19.36	5.34	8.29	14.19	22.69
Average	31.51	18.96	5.14	8.30	14.55	22.51
Minimum	30.14	18.30	4.91	8.10	14.14	21.52

Figures shown above are ultimate failure loads not recommended working loads. As metal properties vary, the above figures are to be used as a guide only.

TRI-FIXX PTY. LTD.
Melbourne
 26-30 Howleys Road
 Notting Hill VIC 3168
 Ph: 03 9543 8422
 Fax: 03 9543 4431
 Email: sales@trifixx.com.au

Geelong
 7-8 Industry Court
 Lara VIC 3212
 Ph: 03 5282 1755
 Fax: 03 5282 6090
 Email: saleslara@trifixx.com.au

Sydney
 5/63 Glendenning Road
 Glendenning NSW 2761
 Ph: 02 9677 9029
 Ph: 02 9677 9023
 Email: sales@trifixxnsw.com.au